

Options

■ **KCH-14**
Basic Remote Control Head



■ **KRK-6DH**
Dual Control Head Remote Kit



■ **KCT-23**

- DC Power cable
- Medium Power Dash (10 Ft.)
 - High Power Dash (10 Ft.)
 - Medium Power Remote (Pos: 23 Ft. Neg: 3.3 Ft.)
 - High Power Remote (Pos: 23 Ft. Neg: 3.3 Ft.)



■ **KMC-9B**

Desktop Microphone



■ **KCH-15**
Full-featured Remote Control Head



■ **KCT-18**
Ignition Sense Cable



■ **KMC-28**

Keypad Microphone (MIL-SPEC Noise Canceling)



■ **KRK-5**
Single Control Head Remote Kit



■ **KCT-22**
Remote Control Cable 8 / 17 / 25 feet



■ **KES-5**

External Speaker (20W)



■ **KMC-27**

Microphone (MIL-SPEC Noise Canceling)



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications (Preliminary)

Model	TK-5710	TK-5710H
GENERAL		
Frequency Range	136-174 MHz	
Number of Channels	512	
Zones	50	
Max. Channels per Zone	250	
Channel Spacing		
Analog	12.5 / 15 / 20 / 25 / 30 kHz	
Digital	12.5 kHz	
Operating Voltage	13.6V DC ± 20%	13.4V DC ± 20%
Current Drain		
Standby	Less than 0.6A	Less than 0.6A
Receive	Less than 2.2A	Less than 2.2A
Transmit	Less than 15A	Less than 28A
Duty Cycle	Transmit: 20%	
Operating Temperature Range	-22 °F to +140 °F (-30 °C to +60 °C)	
Frequency Stability	± 2.0 ppm (-22 °F to +140 °F)	
Antenna Impedance	50 Ω	
Dimensions (W x H x D) (projections not included)		
RF Deck only	7 x 2-3/8 x 7-3/4 in. (178 x 60 x 195 mm)	7 x 2-3/8 x 12-7/8 in. (178 x 60 x 327 mm)
with KCH-14 or 15	7 x 2-3/8 x 9-1/8 in. (178 x 60 x 231 mm)	7 x 2-3/8 x 14-3/8 in. (178 x 60 x 363 mm)
Weight		
(net)	5 lbs. (2.3 kg)	7.9 lbs. (3.6 kg)
with KCH-14	5.7 lbs. (2.6 kg)	8.6 lbs. (3.9 kg)
with KCH-15	5.7 lbs. (2.6 kg)	8.6 lbs. (3.9 kg)
FCC ID	K4435753110	K4435753210
IC Certification	282F-35753110	

Analog measurements made per TIA/EIA 603
Digital measurements made per TIA/EIA 102CAAA
(* 148MHz ~ 168MHz)

FleetSync® is a registered trademark of Kenwood Corporation.
Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.
IMBE™ is a trademark of Digital Voice Systems Inc.

Model	TK-5710	TK-5710H
RECEIVER		
Sensitivity		
Digital (5% BER)	0.25 μV	
Digital (1% BER)	0.40 μV	
Analog 12 dB SINAD	0.25 μV	
Selectivity		
Digital	-60 dB	
Analog @ 25/30 kHz	-83 (85*) dB	
Analog @12.5 kHz	-76 (80*) dB	
Intermodulation Distortion		
Digital	-80 dB	
Analog	-80 dB	
Spurious & Image		
Digital	-90 dB	
Analog	-90 dB	
Audio Output		
Internal (KCH-14)	1.5 W at 8 Ω with less than 3% distortion	
External	12 W at 4 Ω with less than 3% distortion	
External	13 W at 4 Ω with less than 5% distortion	
TRANSMITTER		
RF Power Output	50 W to 5 W	110 W to 50 W
Spurious & Harmonics	80 dB	
FM Hum & Noise		
Analog @ 25 kHz	50 (53*) dB	
Analog @12.5 kHz	45 (47*) dB	
Microphone Impedance	600 Ω	
Audio Distortion	Less than 2%	
Modulation	16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D	

Kenwood follows a policy of continuous advancement in development. For this reason specifications may be changed without notice.

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V, VI	516.4/Procedure I, IV, V, VI	516.5/Procedure I, IV, V, VI
International Protection Standard				
Dust & Water Protection	IP54			

footnotes from Front:
¹ Dual Head remote mounts.
² DTMF Microphone option required.
³ KPG-95D Software required (Windows®98/NT/2000/Me/XP compatible).
⁴ P25 Trunking Option required.
⁵ Operates for 2-Tone, DTMF, FleetSync® selective calling.
⁶ KPG-94 adapts the Motorola® KVL3000/3000 Plus Key Loader to the TK-5710.

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3975 Johns Creek Court, Suite 300, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8



AOS#05905 Printed in USA